

FLSTC HERITAGE SOFTAIL® CLASSIC

MODEL SPECIFICATIONS¹



DIMENSIONS

Length	94.5 in. (2400 mm)
Overall Width	37.6 in. (955 mm)
Overall Height	55.2 in. (1402 mm)

Seat Height:	
• Laden ²	25.5 in. (648 mm)
• Unladen	27.1 in. (688 mm)

Ground Clearance	5.1 in. (130 mm)
------------------	-------------------------

Rake (steering head)	31°
----------------------	-----

Fork Angle	31°
------------	-----

Trail	5.8 in. (147 mm)
-------	-------------------------

Wheelbase	64.5 in. (1638 mm)
-----------	---------------------------

Tires (Dunlop® Harley-Davidson® Series, bias blackwall front and rear):

• Front – D402F	MT90B16 72H
• Rear – D401	150/80B16 71H

Fuel Capacity	5.0 gal. (18.9 L)
<i>(warning light at approximately 1.0 gal.)</i>	

Oil Capacity (w/filter)	3.5 qts. (3.3 L)
-------------------------	-------------------------

Transmission Capacity	1.0 qt. (.95 L)
-----------------------	------------------------

Primary Chain Case Capacity	1.0 qt. (.95 L)
-----------------------------	------------------------

Weight:	
• As Shipped	730 lbs. (331.0 kg)
• In Running Order	761 lbs. (345.0 kg)
• Gross Vehicle Weight Rating	1160 lbs. (526.0 kg)
• Gross Axle Weight Rating:	
• Front	430 lbs. (195.0 kg)
• Rear	730 lbs. (331.0 kg)

ENGINE

Engine	Air-cooled, Twin Cam 103B™
Valves	Pushrod-operated, overhead valves with hydraulic, self-adjusting lifters; two valves per cylinder

Bore x Stroke	3.875 in. x 4.38 in. (98.4 mm x 111.1 mm)
---------------	---

Displacement	103 cu. in. (1690 cc)
--------------	------------------------------

Compression Ratio	9.6:1
-------------------	-------

Fuel System ³	Electronic Sequential Port Fuel Injection (ESPFI)
--------------------------	---

Air Cleaner	Paper, washable
-------------	-----------------

Lubrication System	Pressurized, dry-sump
--------------------	-----------------------

DRIVETRAIN

Primary Drive	Chain, 34/46 ratio
Final Drive	Belt, 32/66 ratio
Clutch	Multi-plate, wet
Transmission	6-Speed Cruise Drive®
Gear Ratios (overall):	U.S.
• 1st	9.311
• 2nd	6.454
• 3rd	4.793
• 4th	3.882
• 5th	3.307
• 6th	2.79

CHASSIS

Frame	Mild steel tubular frame; rectangular section backbone; stamped, cast, and forged junctions; forged fender supports; MIG welded
-------	---

Swingarm	Mild steel, round tube sections, forged junctions; MIG welded
----------	---

Front Forks	41.3 mm telescopic, “beer can” covers
-------------	---------------------------------------

Rear Shocks	Hidden, horizontal-mounted, coil-over
-------------	---------------------------------------

Wheels ⁴ (Tubeless Chrome Aluminum Profile Laced option):	Steel Laced
--	-------------

• Front	16 in. x 3 in. (406 mm x 76 mm)
• Rear	16 in. x 3 in. (406 mm x 76 mm)

Brakes:	
• Caliper Type	4-piston front and 2-piston rear
• Rotor Type	Patented, uniform expansion rotors
(diameter x width):	
• Front	11.5 in. x .2 in. (292 mm x 5.1 mm)
• Rear	11.5 in. x .23 in. (292 mm x 5.8 mm)
• Anti-lock Braking System	Available

Suspension Travel:	
• Front Wheel	5.1 in. (130 mm)
• Rear Wheel	4.3 in. (109 mm)

PERFORMANCE

Engine Torque ⁵ (per J1349):	
• North America	96.9 ft. lbs. @ 3000 RPM (131 Nm @ 3000 RPM)

Lean Angle (per J1168):	
• Right	24.4°
• Left	25.9°

Fuel Economy ⁶ (EPA urban/highway test)	42 mpg (5.6 L/100 km)
--	------------------------------

ELECTRIC

Battery (per Battery Council International Rating)	Sealed, maintenance-free, 12V, 19-amp/hour, 270 cca
Charging	Three-phase, 38-amp system (439W @ 13V, 2000 RPM, 489W max power @ 13V)
Starting	1.2 kW electric with solenoid shift starter motor engagement

Lights (as per country regulation):

• Headlamp (quartz halogen)	55-watt low beam, 60-watt high beam
• Tail/Stop Lights	8W/28W (5W/21W)
• Turn Signal Lights	28W (21W) self-canceling
• Indicator Lamps	High beam, front fender running lights, neutral, low oil pressure, turn signals, engine diagnostics, security system ⁷ (optional), 6-speed, low fuel warnings

WARRANTY

Warranty ⁸	24 months (unlimited mileage)
Service Interval ⁹	First 1000 miles (1600 km), every 5000 miles (8000 km) thereafter

¹ Vehicles depicted may differ from vehicles manufactured and delivered. Specifications and prices listed may differ from specifications and prices of vehicles manufactured and delivered. All product descriptions (including depictions, specifications, dimensions, measurements, ratings and competitive comparisons) are based on available information at the time of publication. Although such descriptions are believed correct, errors and changes can occur and complete accuracy cannot be guaranteed. Harley-Davidson may make changes at any time to prices and specifications, and may change or discontinue models, without notice and without incurring any obligation. Attention: Vehicles in the configurations shown and many of the accessories described in this catalog may not be available for sale or use in some locations. Please check with your dealer for complete product details and the latest information. All models feature 6-speed transmission (V-Rod® models and Sportster® models are 5-speed) and carbon fiber belt final drive; multi-plate clutch with diaphragm spring in oil bath; and 2-year unlimited mileage warranty.

² Measurement reflects **180 lb.** (81.7 kg) operator weight.

³ Recommended 91 octane or higher fuel (R+M)/2.

⁴ Standard and optional wheels may vary by country and region.

⁵ Values shown are nominal. Performance may vary by country and region.

⁶ The combined fuel economy numbers were derived using a combination of estimated city and highway values. Fuel economy estimates are derived from US EPA exhaust emission certification data on a sample motorcycle from the corresponding family under ideal laboratory conditions. Your actual fuel economy will vary depending on your personal riding habits, road and driving conditions, vehicle condition and maintenance, tire pressure, vehicle configuration (parts and accessories), and vehicle loading (cargo, rider and passenger weight). Break-in mileage may vary.

⁷ North America security system includes immobilizer; outside North America the security system includes immobilizer and siren.

⁸ See motorcycle owner's manual for complete details.

⁹ Inspections of certain systems and components are required at 2500 mile (4000 km) intervals. See Owner's Manual for full details.