

FXDC DYNA[®] SUPER GLIDE[®] CUSTOM

MODEL SPECIFICATIONS¹



DIMENSIONS	
Length	92.9 in. (2360 mm)
Overall Width	38.9 in. (988 mm)
Overall Height	48.5 in. (1232 mm)
Seat Height:	
• Laden ²	26.3 in. (668 mm)
• Unladen	26.5 in. (673 mm)
Ground Clearance	4.6 in. (117 mm)
Rake (<i>steering head</i>)	29°
Fork Angle	29°
Trail	4.7 in. (119 mm)
Wheelbase	64.2 in. (1631 mm)
Tires (<i>Michelin[®] Scorcher[®] "31" front and rear</i>):	
• Front – Scorcher [®] "31" 100/90-19 57H	
• Rear – Scorcher [®] "31" 160/70-17 73V	
Fuel Capacity	5.0 gal. (18.9 L) <i>(warning light at approximately 0.9 gal.)</i>
Oil Capacity (<i>w/filter</i>)	3.0 qts. (2.8 L)
Transmission Capacity	1.0 qt. (.95 L)
Primary Chain	1.0 qt. (.95 L)
Case Capacity ³	
Weight:	
• As Shipped	648 lbs. (294.0 kg)
• In Running Order	679 lbs. (308.0 kg)
• Gross Vehicle Weight Rating	1085 lbs. (492.2 kg)
• Gross Axle Weight Rating:	
• Front	390 lbs. (176.9 kg)
• Rear	695 lbs. (315.3 kg)
ENGINE	
Engine	Air-cooled, Twin Cam 96™
Valves	Pushrod-operated, overhead valves with hydraulic, self-adjusting lifters; two valves per cylinder
Bore x Stroke	3.75 in. x 4.38 in. (95.3 mm x 111.3 mm)
Displacement	96 cu. in. (1584 cc)
Compression Ratio	9.2:1
Fuel System ³	Electronic Sequential Port Fuel Injection (ESPFI)
Air Cleaner	Fiberglass Media, washable
Lubrication System	Pressurized, dry-sump

DRIVETRAIN	
Primary Drive	Chain, 34/46 ratio
Final Drive	Belt, 32/66 ratio
Clutch	Multi-plate, wet
Transmission	6-Speed Cruise Drive [®]
Gear Ratios (<i>overall</i>):	U.S.
• 1st	9.311
• 2nd	6.454
• 3rd	4.793
• 4th	3.882
• 5th	3.307
• 6th	2.79

CHASSIS	
Frame	Mild steel, tubular frame; rectangular section backbone; stamped, cast, and forged junctions; forged fender supports; MIG welded
Swingarm	Mild steel, rectangular tube sections, stamped junctions; MIG welded
Front Forks	49 mm with polished aluminum fork triple clamp and dual-rate springs
Rear Shocks	Coil-over shock
Wheels (<i>Chrome Aluminum Profile Laced, front and rear option</i>):	Steel Laced
• Front	19 in. x 2.5 in. (483 mm x 64 mm)
• Rear	17 in. x 4.5 in. (432 mm x 114 mm)
Brakes:	
• Caliper Type	4-piston fixed front, and 2-piston torque-free floating rear
• Rotor Type (<i>diameter x width</i>):	Patented, uniform expansion rotors (floating, front only)
• Front (<i>floating</i>)	11.8 in. x .2 in. (300 mm x 5.1 mm)
• Rear	11.5 in. x .23 in. (292 mm x 5.8 mm)
• Anti-lock Braking System	Available
Suspension Travel:	
• Front Wheel	5 in. (127 mm)
• Rear Wheel	3.1 in. (78.74 mm)

PERFORMANCE	
Engine Torque ⁵ (<i>per J1349</i>):	
• North America	92 ft. lbs. @ 3000 RPM (125 Nm @ 3000 RPM)
Lean Angle (<i>per J1168</i>):	
• Right	29.5°
• Left	30.9°
Fuel Economy ⁶ <i>(EPA urban/highway test)</i>	43 mpg (5.5 L/100 km)

ELECTRIC	
Battery (<i>per Battery Council International Rating</i>)	Sealed, maintenance-free, 12V, 19-amp/hour, 270 cca
Charging	Three-phase, 40-amp system (<i>493W @ 13.5V, 2000 RPM, 540W max power @ 13.5V</i>)
Starting	1.2 kW electric with solenoid shift starter motor engagement
Lights (<i>as per country regulation</i>):	
• Headlamp (<i>quartz halogen</i>)	55-watt low beam, 60-watt high beam
• Tail/Stop Lights	8W/28W
• Turn Signal Lights	28W self-canceling
• Indicator Lamps	High beam, directional light bar, neutral, low oil pressure, engine diagnostics, turn signals, security system ⁷ (<i>optional</i>), 6-speed, low fuel warnings

WARRANTY	
Warranty ⁸	24 months (<i>unlimited mileage</i>)
Service Interval ⁹	First 1000 miles (1600 km), every 5000 miles (8000 km) thereafter

¹ Vehicles depicted may differ from vehicles manufactured and delivered. Specifications and prices listed may differ from specifications and prices of vehicles manufactured and delivered. All product descriptions (including depictions, specifications, dimensions, measurements, ratings and competitive comparisons) are based on available information at the time of publication. Although such descriptions are believed correct, errors and changes can occur and complete accuracy cannot be guaranteed. Harley-Davidson may make changes at any time to prices and specifications, and may change or discontinue models, without notice and without incurring any obligation. Attention: Vehicles in the configurations shown and many of the accessories described in this catalog may not be available for sale or use in some locations. Please check with your dealer for complete product details and the latest information. All models feature 6-speed transmission (V-Rod[®] models and Sportster[®] models are 5-speed) and carbon fiber belt final drive; multi-plate clutch with diaphragm spring in oil bath; and 2-year unlimited mileage warranty.

² Measurement reflects 180 lb. (81.7 kg) operator weight.

³ Recommended 91 octane or higher fuel (R+M)/2.

⁴ Standard and optional wheels may vary by country and region.

⁵ Values shown are nominal. Performance may vary by country and region.

⁶ The combined fuel economy numbers were derived using a combination of estimated city and highway values. Fuel economy estimates are derived from US EPA exhaust emission certification data on a sample motorcycle from the corresponding family under ideal laboratory conditions. Your actual fuel economy will vary depending on your personal riding habits, road and driving conditions, vehicle condition and maintenance, tire pressure, vehicle configuration (parts and accessories), and vehicle loading (cargo, rider and passenger weight). Break-in mileage may vary.

⁷ North America security system includes immobilizer; outside North America the security system includes immobilizer and siren.

⁸ See motorcycle owner's manual for complete details.

⁹ Inspections of certain systems and components are required at 2500 mile (4000 km) intervals. See Owner's Manual for full details.